

**GRENHALL**

**- SAFETY DATA SHEET -**

**SECTION 1: IDENTIFICATION**

**Product Name:** BondTAC S-1430 Waterproof Elastomeric Adhesive Membrane  
**Recommended use:** (Polystyrene-Safe) Waterproof Membrane & Construction Adhesive  
**Restrictions on use:** None

**MANUFACTURER**

Grenhall Industries Inc.  
1 Imperial Court  
Brampton, Ontario, Canada L6T 4X4  
Tel: 905-458-8549  
Fax: 905-458-8363  
[www.grenhall.com](http://www.grenhall.com)

**EMERGENCY CONTACT:**  
**Chemtrec: 1-800-424-9300**  
**Canutec: 613-996-6666**

**SECTION 2: HAZARDS IDENTIFICATION**

GHS Label Elements



Emergency Overview

**Signal Word(s):** DANGER!

**Hazard Statement(s):** Extremely flammable. Vapour harmful.  
May be harmful if swallowed. Causes eye, skin and respiratory tract irritation.

**Precautionary Statements:**

**General:** Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**Hazardous Material Information System (USA):** Health: 2 Flammability: 3 Reactivity: 1  
**National Fire Protection Association (USA):** Health: 2 Flammability: 3 Reactivity: 1

**Relevant routes of exposure:** Eyes, Inhalation, Skin, Ingestion  
**WHMIS hazard class:** B.2, D.2.B

## **Potential Health Effects**

**Inhalation:** Vapours may cause headaches, nausea, dizziness and respiratory tract irritation.  
**Skin Contact:** Irritating to skin.  
**Eye Contact:** Liquid or vapours may irritate the eyes.  
**Ingestion:** Harmful if swallowed.

**Existing conditions aggravated by exposure:** Not available.

## **SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Hazardous Components</b>	<b>CAS NUMBER</b>	<b>%</b>
Naphtha (light aliphatic)	64742-89-8	45 - 55
Toluene	108-88-3	1 - 5

## **SECTION 4: FIRST-AID MEASURES**

**Inhalation:** Move to fresh air. Seek medical attention if complaint persists.  
**Skin Contact:** Wash affected area immediately with soap and water. Seek medical attention, if irritation develops.  
**Eye Contact:** Flush eyes immediately with copious quantities of water for 15 minutes. Seek immediate medical attention.  
**Ingestion:** If swallowed, do not induce vomiting. Seek medical advice immediately.

## **SECTION 5: FIRE-FIGHTING MEASURES**

**Flash point:** -7°C (19.4°F) T.C.C.  
**Autoignition temperature:** Not available  
**Flammability/Explosive limits in air:** 0.8 - 8%(V)  
**Extinguishing Media:** Foam, water spray (fog). Dry chemical powder or carbon dioxide.  
**Special firefighting procedures:** Wear self-contained breathing apparatus. Wear full protective clothing.  
**Unusual fire or explosion hazards:** Vapours may cause flash fire. Vapours may travel along ground to remote ignition source where they can ignite, flashback or explode.  
**Hazardous combustion products:** Carbon dioxide. Carbon monoxide.  
**Sensitivity to static discharge:** Vapours sensitive.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

**Clean-up methods:** Soak up with inert absorbent material and place in a chemical-safe waste container until ready for disposal.

## **SECTION 7: HANDLING AND STORAGE**

**Handling:** Avoid contact with skin, eyes, and clothing. Do not breathe vapour and mist. Wash thoroughly after handling. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

**Storage:** Keep the container tightly closed and store in a cool, dry, ventilated area. Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

## **SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

	<b>Naphtha</b> (light aliphatic)	<b>Toluene</b>
<b>OSHA</b> Permissible Exposure Limit (PEL)	1,000 ppm	200 ppm (TWA) 300 ppm (ceiling conc.) 500 ppm (max. concentration)
<b>ACGIH - TWA</b>	400 ppm (TWA)	50 ppm (skin)

**Engineering Controls:** Use local ventilation if general ventilation is insufficient to maintain vapour concentration below established exposure limits.

**Respiratory Protection:** Use NIOSH approved respirator if there is potential to exceed exposure limits.

**Eye/face Protection:** Safety goggles or safety glasses with side shields.

**Skin Protection:** Use impermeable gloves and protective clothing as necessary to prevent skin contact.

**Personal Protective Equipment:** Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits. Eye washes and showers for emergency use.

**Additional Information:** Wash hands before eating, drinking, or using the toilet.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Yellow
Odour:	Solvent
Odour threshold:	Not available
Vapour pressure:	Not available
Specific gravity:	0.83
Vapor density (Air=1):	Above 1
Flash point:	-7°C T.C.C.
Autoignition temperature:	Not available
Evaporation rate (Butyl Acetate=1):	Greater (faster than)
Evaporation rate (Ethyl Acetate=1):	Less (slower than)
Solubility in water:	Not soluble
% Non-Volatiles:	42 - 46
Viscosity:	400 - 600 cps

## SECTION 10: STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of use.
Conditions to Avoid:	Avoid heat, sparks, open flames and other ignition sources.
Materials to Avoid:	Strong oxidizing agents.

## SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological testing has not been conducted for the overall product. The data shown below is representative for the individual hazardous ingredients.

COMPONENT	LD <sub>50</sub>	LC <sub>50</sub>
Naphtha (light aliphatic)	>2,000 mg/g, oral Rat	>5,000 ppm
Toluene	>2g/kg oral, rat >2g/kg skin, rabbit	8,000 ppm, rat

## SECTION 12: ECOLOGICAL INFORMATION

Ecological information: Not available.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Material Disposal:** Destroy by incineration at an approved waste facility.

**Container Disposal:** Drain container thoroughly and vent in a safe place away from sparks and fire. Refer to Section 7 before handling the product or containers. Residue may present an explosion hazard.

## SECTION 14: TRANSPORT INFORMATION

Transportation Classification: (DOT/TDG/IMDG/IMO/ICAO/IATA)

Identification Number: UN1133

Proper Shipping Name: ADHESIVES containing flammable liquid  
Hazard Class or Division: 3  
Packing Group: II

## **SECTION 15: REGULATORY INFORMATION**

### **Canada Regulatory Information:**

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

This product has been classified in accordance with the hazard criteria of the CPR  
W.H.M.I.S. Classification: B2, D2A, D2B

### **United States Regulatory Information:**

TSCA 8 (b) Inventory Status: All components are listed on or are exempt from listing on the Toxic Substances Control Act Inventory.

SARA Title III Section 313 Form "R"/TRI Reportable Chemical

### **Other Regulations:**

SARA Hazard Classes: Fire Hazard.

## **SECTION 16: OTHER INFORMATION**

Issue Date: May 2015  
Supersedes Date: April 2014  
Revision Information: New Format